

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):


- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

0306-D

103876



Europäisches Patentamt
European Patent Office
Office européen des brevets



Publication number: 0 680 201 A2

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 95106254.6

(51) Int. Cl.⁶: H04N 1/62

(22) Date of filing: 26.04.95

(30) Priority: 27.04.94 JP 90281/94
20.04.95 JP 95201/95

(43) Date of publication of application:
02.11.95 Bulletin 95/44

(84) Designated Contracting States:
DE ES FR GB IT NL SE

(71) Applicant: CANON KABUSHIKI KAISHA
30-2, 3-chome, Shimomaruko,
Ohta-ku
Tokyo (JP)

(72) Inventor: Yui, Hideaki, c/o Canon K.K.
30-2, 3-chome, Shimomaruko
Ohta-ku,
Tokyo 146 (JP)


(74) Representative: Pellmann, Hans-Bernd,
Dipl.-Ing. et al
Patentanwaltsbüro
Tiedtke-Bühling-Kinne & Partner
Bavariaring 4
D-80336 München (DE)

(54) Image processing apparatus and method.

(57) An image processing apparatus of this invention has an ordinary displaying mode and a hue conversion mode to change hues in correspondence with a user. In the ordinary displaying mode, input image

data is displayed on a display, and in the hue conversion mode, an image for hue conversion is displayed on the display. The hues are converted in accordance with an instruction of the user.

FIG. 1



EP 0 680 201 A2

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to an image processing apparatus and, more particularly, to an image processing apparatus for converting a video signal into a signal for a display panel.

Related Background Art

As is conventionally known, the hues of CRT video output signals are determined in correspondence with the statistically determined luminous efficiency (the energy distribution amounts of R, G, and B sensed by the human eyes).

In color digital video signal processing, a series of processing operations such as gamma conversion, color management, and the like, which take the characteristics of an input/output display device and matching to the color reproducibility of color peripheral apparatuses represented by a printer and scanner into account are performed in consideration of the statistically determined visual sense characteristics of normal persons.

However, when the hues are determined in correspondence with the statistically determined luminous efficiency, it is inconvenient for, e.g., red-blind or color-blind persons, or a person who wants to intentionally change hues, resulting in a low degree of freedom. Since it is known that Europeans and Americans tend to be sensitive to red, and Japanese tend to be sensitive to blue, it is often inconvenient to determine the hues in correspondence with the statistically determined luminous efficiency.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide an image processing apparatus which can change hues to solve the above-mentioned problems.

According to the present invention, there is provided an image processing apparatus with a display panel, comprising video signal generation means for generating a video signal, color sense conversion means for color-sense-converting the video signal generated by the video signal generation means on the basis of predetermined color sense data, and signal conversion means for converting the video signal color-sense-converted by the color sense conversion means into a signal for the display panel.

According to the present invention, there is also provided an image processing apparatus for converting an input image signal into an output image signal using a color conversion table, com-

prising switching means for selecting one of first and second modes, and display control means for displaying an image input by input means on display means when the first mode is selected, and displaying information for changing the color conversion table on the display means when the second mode is selected.

With the above arrangement, a video signal is generated by the video signal generation means, the generated video signal is color-sense-converted by the color sense conversion means on the basis of color sense data. The converted video signal is converted into a signal for the display panel by the signal conversion means.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram of the overall image processing apparatus according to the first embodiment of the present invention;

Fig. 2 is comprised of Fig. 2A and Fig. 2B showing flow charts of color table data generation/registration processing in the first embodiment;

Figs. 3A-1 to 3C-2 are views showing the custom conversion processing of R, G, and B input/output characteristics;

Fig. 4 is a block diagram of the overall image processing apparatus according to the second embodiment of the present invention;

Figs. 5A to 5C are views showing input and output color spaces in the second embodiment;

Figs. 6A-1 to 6C-2 are views showing the custom conversion processing of R, G, and B input/output characteristics;

Fig. 7 is a block diagram of the overall image processing apparatus according to the third embodiment of the present invention;

Fig. 8 is a block diagram showing the arrangement of a color sense processor; and

Fig. 9 is a block diagram of the overall image processing apparatus according to the fourth embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The preferred embodiments of the present invention will be described hereinafter with reference to the accompanying drawings.

(First Embodiment)

Fig. 1 is a block diagram showing the overall image processing apparatus according to the first embodiment of the present invention.

Referring to Fig. 1, digital R, G, and B input data 1 are supplied from a video signal output

terminal of an information processing apparatus such as a work station, a personal computer, or the like. A selector 2 switches between custom table address data 8 supplied from a controller 7, and the digital R, G, and B input data 1. A color conversion table 3 comprises a rewritable RAM which stores color conversion table data 14 supplied from the controller 7, and looks up data (address) supplied from the selector 2 to output table data 4 based on the looked-up data. A display controller 5 controls the display operation of a display 6 as an output display device on the basis of the table data 4 supplied from the color conversion table 3. A color conversion table generator 10 changes setting data of table data on the basis of variable information of an RGB control dial 11 when a user of this apparatus wants to generate custom color conversion data. A custom information input device 13 comprises a keyboard used for inputting the personal ID information of a user of this apparatus, a magnetic card, and the like. A custom table memory 9 is a storage device which stores custom table data generated by the color conversion table generator 10, and comprises, e.g., a hard disk device, a floppy disk device, and the like. A comparator 12 compares the personal ID information input from the custom information input device 13 with the registered contents of the custom table memory 9.

The operation of the first embodiment will be described below. In ordinary image processing of this apparatus, the digital R, G, and B input data 1 are selected by the selector 2, and are supplied to the color conversion table 3 as addresses. Based on the addresses, data, which are pre-stored in the color conversion table and correspond to the input addresses, are output as the table data 4. The table data 4 are converted into a transfer format compatible with the display by the display controller 5, and the converted data are transferred to the display 6 together with a driving control signal. This processing flow is the same as that of ordinary color conversion processing, and it is a common practice to rewrite and change the contents of the color conversion table upon execution of color conversion processing such as inverse gamma correction in correspondence with the characteristics of the connected display. The flow of the above-mentioned ordinary processing takes only the visual sense characteristics of average persons, the characteristics of the display, and the like.

Processing for customizing color conversion in units of users as the characteristic feature of the present invention will be explained below.

First, a user generates and registers color conversion table data customized for himself or herself. The processing flow will be explained below with reference to the flow charts shown in Figs. 2A

and 2B.

Figs. 2A and 2B are flow charts showing color table data generation/registration processing.

When the above-mentioned ordinary data displaying operation is performed (step S1), the color conversion table generator 10 checks if the user turns on a table control button of the RGB control dial 11 (step S2). If NO in step S2, the ordinary data displaying operation is performed. However, if it is determined in step S2 that the user turns on the table control button, an R-table control image is displayed on the display 6 in step S3. At this time, the color conversion table generator 10 outputs a display request of an R-table control image to the controller 7. Upon reception of this request, the controller 7 switches the selector 2 to the custom table address data 8 side, and reads out an R-scale color bar image as the R-table control image from the custom table memory 9. The R-scale color bar image is displayed on the display 6 via the color conversion table 3 and the display controller 5. At this time, the table data stored in the color conversion table are tuned by the controller 7 to have linear input/output characteristics which can serve as standard data for control, as shown in Fig. 3A-1. It is checked in step S4 if a change request of an R-table is input. If NO in step S4, the flow jumps to step S6. Upon adjustment of the R-table, the user adjusts the RGB control dial 11 while observing the R-scale color bar image displayed on the display 6, thereby changing the characteristics of table data as the user desired. During this adjustment, the contents of the color conversion table 3 can be rewritten by the controller 7 as needed, and the user can perform operations while confirming the adjustment result (effect) on the screen of the display 6. Fig. 3A-2 shows an example of the input/output characteristics of the R-table which are changed by the adjustment. The characteristics of a G-table are also changed from Fig. 3B-1 to Fig. 3B-2 by the same processing (steps S7 and S8), and the characteristics of a B-table are changed from Fig. 3C-1 to Fig. 3C-2 by the same processing (steps S10 and S11). With the above-mentioned processing, all the R, G, and B color conversion table data are customized. If it is determined in step S12 that the user turns on a custom registration button of the RGB control dial 11, the R, G, and B custom table data adjusted in steps S5, S8, and S11 are stored in the custom table memory 9 in step S13. At this time, the user simultaneously inputs an index ID of the registered data from the custom information input device 13, thus completing registration of custom table data. Subsequently, when the user turns off the table control button of the RGB control dial 11 (step S14), the flow returns to step S1 to resume the ordinary data displaying mode. At this time, the data in the

conversion table 3 have already been changed to the latest data (the data adjusted in steps S5, S8, and S11).

Processing for changing the contents of the color conversion table 3 when the user uses this apparatus will be described below.

Referring to Fig. 1, the user inputs personal ID information from the custom information input device 13, and transfers it to the comparator 12. The comparator 12 transfers a comparison request to the controller 7. Upon reception of this request, the controller 7 loads and scans all index IDs of already registered data from the custom table memory 9, and transfers them to the comparator 12. Upon reception of these data, the comparator 12 performs comparison processing. If the comparator 12 cannot find any coincidence, it informs non-coincidence to the user. If a coincidence is found, the comparator 12 outputs a download request to the controller 7 to download the R, G, and B custom table data corresponding to the index ID from the custom table memory 9 to the color conversion table 3.

With the above-mentioned processing, color conversion processing customized in units of users can be realized.

(Second Embodiment)

Fig. 4 is a block diagram showing the overall image processing apparatus according to the second embodiment. The apparatus shown in Fig. 4 is substantially the same as that in Fig. 1, except that host profile information 20 and display profile information 21 are input to the controller 7.

Referring to Fig. 4, the host profile information includes color space information of R, G, and B input data which can be reproduced by the host side. The display profile information includes color space information of R, G, and B output data, which can be reproduced by the display side. These two pieces of information are transferred to the controller 7, and the controller 7 executes the following processing.

(1) When Host Color Space = Display Color Space

Fig. 5A shows a color space in this case.

In this case, it is determined that the host color space is the same as the display color space, and the contents of the color conversion table are customized according to a user's request by the processing of the first embodiment while maintaining the host color space.

(2) When Host Color Space < Display Color Space

Fig. 5B shows a color space in this case.

In this case, it is determined that the display color space is larger than the host color space (the color space reproducing performance of the display color space is higher than that of the host color space), and the contents of the color conversion table are customized according to a user's request by the processing of the first embodiment while maintaining the host color space.

(3) When Host Color Space > Display Color Space

Fig. 5C shows a color space in this case.

In this case, it is determined that the display color space is smaller than the host color space (the color space reproducing performance of the display color space is lower than that of the host color space), and the following clipping processing is performed prior to the custom processing according to a user's request. More specifically, processing for assigning all color space portions, which cannot be reproduced by the display side, to the closest portions in the host color space (clipping processing) is performed. The controller 7 performs the clipping processing, and writes new color conversion data generated after the clipping processing in the color conversion table 3. The input/output characteristics written in the color conversion table 3 are as shown in Figs. 6A-1, 6B-1, and 6C-1. Upon adjustment of the RGB control dial from this state by the processing of the first embodiment, portions other than the clipped portions are adjusted, and color conversion processing which is optimally customized in consideration of the color reproduction performances of both the host and display sides is performed, as shown in Figs. 6A-2, 6B-2, and 6C-2.

(Third Embodiment)

Fig. 7 is a block diagram showing the overall image processing apparatus according to the third embodiment of the present invention.

Referring to Fig. 7, a host graphic card 71 as video signal generation means outputs graphic data generated by an information processing apparatus such as a work station, a personal computer, or the like. An image converter 74 converts an analog video signal VIDEO and horizontal/vertical synchronization signals (Hsync/Vsync) supplied from the host graphic card 71 into signals for a display panel 75.

An external input device 72 as color sense data input means is used for inputting, to the image converter 74, data stored in a storage medium comprising, e.g., a magnetic card, which stores

personal color sense (spectral sensitivity) data generated in advance, as described in the first embodiment. A switch 73 is used for selecting one of an ordinary processing mode and a processing mode based on personal color sense data.

The image converter 74 comprises an AD converter 76, a selector 79, a color space converter 77 as signal conversion means, a binarizer/buffer 78, a color sense processor 80 as color sense conversion means, and an external input device interface (I/F) 81.

The AD converter 76 includes an A/D converter, and other circuits, and performs horizontal/vertical timing detection, data extraction, and the like from the analog video signal VIDEO and the horizontal/vertical synchronization signals (Hsync/Vsync) supplied from the host graphic card 71 using synchronization separation and PLL (phase-locked loop), thereby converting input data into an image data format required in the subsequent processing.

The selector 79 connects the output from the AD converter 76 to the color space converter 77 when the processing mode based on color sense data is selected by the switch 73, and connects the output from the AD converter 76 to the color sense processor 80 when the ordinary processing mode is selected by the switch 73.

The color sense processor 80 color-sense-converts a video signal from the selector 79 on the basis of color sense data input from the external input device 82 via the external input device interface 81.

The color space converter 77 performs clipping processing of a video signal from the selector 79 or the color sense processor 80 to a color space optimal to the display panel 75.

The binarizer/buffer 78 performs format conversion and buffering of data with respect to the display panel 75.

Fig. 8 is a block diagram showing the arrangement of the color sense processor 80 shown in Fig. 7.

Referring to Fig. 8, a spectral sensitivity standardizer 84 converts the spectral sensitivity of data into that of average persons to obtain standardized spectral sensitivity data as pre-processing of conversion since the spectral sensitivity of actually input data may be calibrated in correspondence with a race or personal difference.

A controller 85 processes personal spectral sensitivity data read out from the external input device 72 to convert it into control data for spectral sensitivity conversion processing.

A spectral sensitivity conversion processor 86 comprises a look-up table memory (LUT ROM) 88 and a decoder 87. In this processor 86, a control signal from the controller 85 is decoded by the

decoder 87, and the LUT ROM 88 is controlled by the output from the decoder 87, thereby generating personal spectral sensitivity data.

The operation of the image processing apparatus of the third embodiment will be described below.

The analog video signal VIDEO and the horizontal/vertical synchronization signals (Hsync/Vsync) supplied from the host graphic card 71 are input to the image converter 74, and are subjected to horizontal/vertical timing detection, data extraction, and the like using synchronization separation and PLL in the AD converter 76. When the switch 73 selects the processing mode based on color sense data, the output from the AD converter 76 is connected to the color space converter 77 by the selector 79; when the ordinary processing mode is selected, the output from the AD converter 76 is connected to the color sense processor 80.

In the ordinary processing mode, the color space converter 77 performs clipping processing to a color space optimal to the display panel 75, the binarizer/buffer 78 performs format conversion and buffering of data with respect to the display panel 75, and the display panel 75 is driven based on the buffered data.

On the other hand, in the processing mode based on color sense data, the color sense processor 80 color-sense-converts the video signal on the basis of personal color sense data stored in the storage medium of the external input device 72. The color space converter 77 performs clipping processing of the converted video signal to a color space optimal to the display panel 75, the binarizer/buffer 78 performs format conversion of data with respect to the display panel 75, and the display panel 75 is driven based on buffered data.

(Fourth Embodiment)

Fig. 9 is a block diagram showing the overall image processing apparatus according to the fourth embodiment of the present invention. The same reference numerals in Fig. 9 denote the same parts as in Fig. 7.

An image converter 94 comprises an AD converter 76, a selector 79, a color space converter 77, a binarizer/buffer 78, a color sense processor 80, an external input device interface 81, a personal code comparator 91 as searching means, and an internal memory 92 as storage means. The image converter 94 is electrically connected to a host graphic card 71, a display panel 75, an external input device 72, and a switch 73 as in the image converter 74 shown in Fig. 7.

An external input device 90 as identification data input means comprises, e.g., a ten-key pad,

and is used for inputting a user code to the personal code comparator 91.

This embodiment is different from the third embodiment in the following points. More specifically, in this embodiment, when a user who initially uses the system inputs personal spectral sensitivity data from the external input device 72 and inputs a user code from the external input device 90, the personal code comparator 91 stores the personal spectral sensitivity data in the internal memory 92 in correspondence with the user code.

Also, in this embodiment, when a user inputs only a user code from the external input device 90, the personal code comparator 91 searches the internal memory 92. When the comparator 91 finds the input user code, personal spectral sensitivity data corresponding to the input user code is read out, and the readout personal spectral sensitivity data is input to the color sense processor 80 via the external input device interface 81.

As described above, according to this embodiment, a system user need not perform calibration using personal color sense data each time he or she uses the system, and the operability of the user environment can be improved for a plurality of users who share a single system.

Since the means for inputting a user code and the means for searching the contents of a registration database are arranged, the color sense data of a user himself or herself are not exposed to a third party, thus improving the confidentiality of personal information.

Even for users having color senses different from the statistically determined color sense data, an output image optimized for each user can be obtained.

Since data input/output color spaces are looked up, and matching processing is attained by optimal clipping processing based the looked-up color spaces as pre-processing of custom data calibration, a system user can perform customized color conversion of the connected environment of a color system with optimal color reproducibility.

An image processing apparatus of this invention has an ordinary displaying mode and a hue conversion mode to change hues in correspondence with a user. In the ordinary displaying mode, input image data is displayed on a display, and in the hue conversion mode, an image for hue conversion is displayed on the display. The hues are converted in accordance with an instruction of the user.

Claims

1. An image processing apparatus with a display panel, comprising:
video signal generation means for generat-

ing a video signal;

color sense conversion means for color-sense-converting the video signal generated by said video signal generation means on the basis of predetermined color sense data; and

signal conversion means for converting the video signal color-sense-converted by said color sense conversion means into a signal for the display panel.

2. An apparatus according to claim 1, further comprising color sense data input means for inputting the predetermined color sense data.
3. An apparatus according to claim 1, further comprising:
storage means for storing the predetermined color sense data in correspondence with identification data;
identification data input means for inputting identification data; and
searching means for searching said storage means to find color sense data corresponding to the identification data input by said identification input means.
4. An image processing apparatus for converting an input image signal into an output image signal using a color conversion table, comprising:
switching means for selecting one of first and second modes; and
display control means for displaying an image input by input means on display means when the first mode is selected, and displaying information for changing the color conversion table on the display means when the second mode is selected.
5. An image processing method of converting an input image signal into an output image signal using a color conversion table, comprising the steps of:
selecting one of first and second modes on the basis of an instruction from input means;
displaying an image input by image input means on display means when the first mode is selected, and displaying information for changing the color conversion table on the display means when the second mode is selected; and
displaying an image input by the image input means using the changed color conversion table.

FIG. 1




FIG. 2A




FIG. 2

FIG. 2A

FIG. 2B

FIG. 2B





FIG. 3A-1 FIG. 3B-1 FIG. 3C-1



S21
ADJUST
R-LEVEL
↓

S24
ADJUST
G-LEVEL
↓

S27
ADJUST
B-LEVEL
↓

FIG. 3A-2 FIG. 3B-2 FIG. 3C-2





FIG. 4









FIG. 6A-1 FIG. 6B-1 FIG. 6C-1



ADJUST
R-LEVEL

ADJUST
G-LEVEL

ADJUST
B-LEVEL

FIG. 6A-2 FIG. 6B-2 FIG. 6C-2




FIG. 7




FIG. 8






FIG. 9





Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 680 201 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
05.06.1996 Bulletin 1996/23

(51) Int. Cl.⁶: H04N 1/62

(43) Date of publication A2:
02.11.1995 Bulletin 1995/44

(21) Application number: 95106254.6

(22) Date of filing: 26.04.1995

(84) Designated Contracting States:
DE ES FR GB IT NL SE

(30) Priority: 27.04.1994 JP 90281/94
20.04.1995 JP 95201/95

(71) Applicant: CANON KABUSHIKI KAISHA
Tokyo (JP)

(72) Inventor: Yui, Hideaki,
c/o Canon K.K.
Ohta-ku, Tokyo 146 (JP)


(74) Representative: Pellmann, Hans-Bernd, Dipl.-Ing.
et al
Patentanwaltsbüro
Tiedtke-Bühling-Kinne & Partner
Bavariaring 4
80336 München (DE)

(54) Image processing apparatus and method

(57) An image processing apparatus of this invention has an ordinary displaying mode and a hue conversion mode to change hues in correspondence with a user. In the ordinary displaying mode, input image data is dis-

played on a display, and in the hue conversion mode, an image for hue conversion is displayed on the display. The hues are converted in accordance with an instruction of the user.

FIG. 1



EP 0 680 201 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 95 10 6254

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	EP-A-0 546 773 (XEROX CORPORATION) * abstract; figures 1,3 * * column 3, line 17 - line 32 * ---	1-5	H04N1/62
A	EP-A-0 590 763 (SCITEX CORPORTION) * abstract; figures * ---	1-5	
A	EP-A-0 310 388 (CROSFIELD ELECTRONICS) * the whole document * ---	1-5	
A	WO-A-92 20184 (EASTMAN KODAK) * abstract; figures * -----	1-5	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			H04N
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 9 April 1996	Examiner Isa, S
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ----- & : member of the same patent family, corresponding document</p>			

EPO FORM 150 (03.02.1994) (P04/C01)